




法兰通径 DN	JB/ T81-59/HG5010-58									螺栓孔 中心距	螺栓孔 直径	螺栓孔 数量
	法兰外径	法兰内径B		内凸圆直径	内凸圆厚度	法兰厚度	法兰盖厚度	密封面尺寸				
	D	A管	B管	B1	f1	b	b1	D2	f			
Pg=6公斤/厘米 ²												
10	75	18	15	-	-	12	12	32	2	50	12	4
15	80	22	19	-	-	12	12	40	2	55	12	4
20	90	27.5	26	-	-	14	12	50	2	65	12	4
25	100	34.5	33	-	-	14	12	60	2	75	12	4
32	120	43.5	39	-	-	16	12	70	2	90	14	4
40	130	49.5	46	40	4	16	14	80	3	100	14	4
50	140	61.5	59	50	4	16	14	90	3	110	14	4
65	160	77.5	78	65	4	16	14	110	3	130	14	4
80	185	90.5	91	80	4	18	14	125	3	150	18	4
100	205	116	110	100	4	18	14	145	3	170	18	4
125	235	141.5	135	125	4	20	16	175	3	200	18	8
150	260	170.5	161	150	4	20	16	200	3	225	18	8
175	290	-	196	-	5	22	16	230	3	255	18	8
200	315	221.5	222	208	6	22	16	255	3	280	18	8
225	340	-	248	-	6	22	16	280	3	305	18	8
250	370	276.5	276	255	7	24	16	310	3	335	18	12
300	435	327.5	328	308	7	24	18	362	4	395	23	12
350	485	359.5	380	340	8	26	18	412	4	445	23	12
400	535	411	430	408	8	28	20	462	4	495	23	16
450	590	462	484	455	8	28	22	518	4	550	23	16
500	640	513.5	534	505	9	30	24	568	4	600	23	16
600	755	616.5	634	605	9	30	28	670	5	705	25	20
700	860	715	724	705	9	32	32	775	5	810	25	24
800	975	817	824	810	9	32	36	880	5	920	30	24
900	1075	918	924	900	-	34	40	980	5	1020	30	24
1000	1175	1020	1024	1000	10	36	44	1080	5	1120	30	28
1200	1400	1223	1224	1200	10	40	60	1295	5	1340	34	32
1400	1620	1426	1424	1400	12	44	68	1510	5	1560	34	36
1500	1720	-	1524	1500	12	46	-	1610	5	1660	34	36
1600	1820	1630	1624	1600	14	48	76	1710	5	1760	34	40
1800	2045	1833	1824	1800	-	50	84	1910	5	1970	41	44
2000	2265	2036	2024	2000	-	54	92	2110	5	2180	48	48
2200	2475	-	2224	2200	-	60	-	2330	6	2390	48	52
2400	2685	-	2424	-	-	62	-	2540	6	2600	48	56
2600	2900	-	2624	-	-	64	-	2740	6	2850	48	60
2800	3110	-	2824	-	-	68	-	2950	6	3020	48	64
3000	3310	-	3024	-	-	70	-	3150	6	3220	48	68
3200	3520	-	3224	-	-	76	-	3360	6	3430	48	72
3400	3730	-	3424	-	-	80	-	3570	6	3640	48	76
3600	3970	-	3624	-	-	84	-	3780	6	3860	56	80

法兰通径 DN	JB/ T81-59/HG5010-58									螺栓孔 中心距	螺栓孔 直径	螺栓孔 数量
	法兰外径	法兰内径B		内凸圆直径	内凸圆厚度	法兰厚度	法兰盖厚度	密封面尺寸				
	D	A管	B管	B1	f1	b	b1	D2	f			
Pg=10公斤/厘米²												
10	90	18	15	-	-	12	12	40	2	60	14	4
15	95	22	19	-	-	12	12	45	2	65	14	4
20	105	27.5	26	-	-	14	12	55	2	75	14	4
25	115	34.5	33	-	-	14	12	65	2	85	14	4
32	135	43.5	39	-	-	16	12	78	2	100	18	4
40	145	49.5	46	40	4	18	14	85	3	110	18	4
50	160	61.5	59	50	4	18	14	100	3	125	18	4
65	180	77.5	78	65	4	20	14	120	3	145	18	4
80	195	90.5	91	80	4	20	14	135	3	160	18	4
100	215	116	110	100	4	22	14	155	3	180	18	8
125	245	141.5	135	125	4	24	16	185	3	210	18	8
150	280	170.5	161	150	4	24	16	210	3	240	23	8
175	310	-	196	-	5	24	16	240	3	270	23	8
200	335	221.5	222	208	5	24	16	265	3	295	23	8
225	365	-	248	-	6	24	18	295	3	325	23	8
250	390	276.5	276	255	6	26	18	320	3	350	23	12
300	440	327.5	328	308	6	28	20	368	4	400	23	12
350	500	359.5	380	340	7	28	24	428	4	460	23	16
400	565	411	430	408	7	30	26	482	4	515	25	16
450	615	462	484	455	7	30	28	532	4	565	25	20
500	670	513.5	534	505	8	32	32	585	4	620	25	20
600	780	616.5	634	605	8	36	36	685	5	725	30	20
700	895	715	724	705	9	38	42	800	5	840	30	24
800	1010	817	824	810	9	40	48	905	5	950	34	24
900	1110	918	924	900	9	44	54	1005	5	1050	34	28
1000	1220	1020	1024	1000	9	48	58	1115	5	1160	34	28
1200	1450	1223	1224	1200	10	52	-	1325	5	1380	41	32
1400	1675	1426	1424	1400	10	62	-	1525	5	1590	48	36
1600	1915	1630	1624	1600	12	63	-	1750	5	1820	54	40
1800	2115	1833	1824	1800	12	70	-	1950	5	2020	54	44
2000	2325	2036	2024	2000	14	74	-	2160	5	2230	54	48

(mm)

法兰通径 DN	JB/ T81-59/HG5010-58									螺栓孔 中心距	螺栓孔 直径	螺栓孔 数量
	法兰外径	法兰内径B		内凸圆直径	内凸圆厚度	法兰厚度	法兰盖厚度	密封面尺寸				
	D	A管	B管	B1	f1	b	b1	D2	f			
Pg=16公斤/厘米²												
10	90	18	15	-	-	14	12	40	2	60	14	4
15	95	22	19	-	-	14	12	45	2	65	14	4
20	105	27.5	26	-	-	16	12	55	2	75	14	4
25	115	34.5	33	-	-	18	12	65	2	85	14	4
32	135	43.5	39	-	-	18	12	78	2	100	18	4
40	145	49.5	46	40	4	20	14	85	3	110	18	4
50	160	61.5	59	50	4	22	14	100	3	125	18	4
65	180	77.5	78	65	4	24	14	120	3	145	18	4
80	195	90.5	91	80	4	24	14	135	3	160	18	8
100	215	116	110	100	4	26	16	155	3	180	18	8
125	245	141.5	135	125	4	28	16	185	3	210	18	8
150	280	170.5	161	150	4	28	18	210	3	240	23	8
175	310	-	196	-	5	28	18	240	3	270	23	8
200	335	221.5	222	208	5	30	20	265	3	295	23	12
225	365	-	248	-	6	30	22	295	3	325	23	12
250	405	276.5	276	255	6	32	24	320	3	355	25	12
300	460	327.5	328	308	6	32	28	375	4	410	25	12
350	520	359.5	380	340	7	34	32	435	4	470	25	16
400	580	411	430	405	7	38	36	485	4	525	30	16
450	640	462	484	455	8	42	42	550	4	585	30	20
500	705	513.5	534	505	8	48	46	608	4	650	34	20
600	840	616.5	634	605	8	50	50	718	5	770	41	20
700	910	715	724	705	9	50	-	788	5	840	41	24
800	1020	817	824	810	9	52	-	898	5	950	41	24
900	1120	918	924	900	10	44	-	998	5	1050	41	28
1100	1370	-	1124	1100	10	50	-	1222	5	1280	42	28
1200	1485	1223	1224	1200	10	52	-	1325	5	1390	54	32
1400	1685	1426	1424	1400	12	58	-	1525	5	1590	54	36
1600	1930	1630	1624	1600	14	64	-	1750	5	1820	58	40
1800	2130	1833	1824	1800	16	68	-	1950	5	2020	58	44
2000	2345	2036	2024	2000	18	70	-	2150	5	2230	62	48

(mm)

法兰通径 DN	JB/ T81-59/HG5010-58									螺栓孔 中心距	螺栓孔 直径	螺栓孔 数量
	法兰外径	法兰内径B		内凸圆直径	内凸圆厚度	法兰厚度	法兰盖厚度	密封面尺寸				
	D	A管	B管	B1	f1	b	b1	D2	f			
Pg=25公斤/厘米²												
10	90	18	15	-	-	16	12	40	2	60	14	4
15	95	22	19	-	-	16	12	45	2	65	14	4
20	105	27.5	26	-	-	18	12	55	2	75	14	4
25	115	34.5	33	-	-	18	12	65	2	85	14	4
32	135	43.5	39	-	-	20	12	78	2	100	18	4
40	145	49.5	46	40	4	22	14	85	3	110	18	4
50	160	61.5	59	50	4	24	14	100	3	125	18	4
65	180	77.5	78	65	4	24	16	120	3	145	18	8
80	195	90.5	91	80	4	26	18	135	3	160	18	8
100	230	116	110	100	4	28	20	160	3	190	23	8
125	270	141.5	135	125	4	30	22	188	3	220	25	8
150	300	170.5	161	150	4	30	24	218	3	250	25	8
175	330	-	196	-	5	32	24	248	3	280	25	12
200	360	221.5	222	208	6	32	26	278	3	310	25	12
225	395	-	248	-	6	34	28	302	3	340	30	12
250	425	276.5	276	255	7	34	30	332	3	370	30	12
300	485	327.5	328	308	7	36	34	390	4	430	30	16
350	550	359.5	380	340	8	42	38	448	4	490	34	16
400	610	411	430	408	8	44	42	505	4	550	34	16
450	660	462	484	455	8	48	46	555	4	600	34	20
500	730	513.5	534	505	9	52	48	610	4	660	41	20
600	840	616.5	634	605	9	56	58	718	5	770	41	20
700	955	715	724	705	9	60	-	815	5	870	48	24
800	1070	817	824	810	9	64	-	930	5	990	48	24
900	1180	918	924	900	-	66	-	1025	5	1090	54	28
1000	1320	1020	1024	1000	10	68	-	1140	5	1210	58	28
1200	1525	1223	1224	1200	12	72	-	1350	5	1420	58	32
1400	1750	1426	1424	1400	12	78	-	1560	5	1640	62	36
1600	1975	1630	1624	1600	14	84	-	1780	5	1860	62	40
1800	2195	1833	1824	1800	-	90	-	1985	5	2070	70	44
2000	2425	2036	2024	2000	-	96	-	2210	5	2300	70	48